






	! " #	\$! % & '	! () % * +	, -	. /
	! "#\$%				
&	! !\$' "\$"	"	0 1 2 3 4 5 6 7 8 9 : 5 6 ; <	= >	? @ A
(	! \$ % \$)	* ++	BC 4 , - . / 9 0 1) DE 3 4 FG ; < H I J K L (0 1 \$ / " ! " 7 M N O P Q R S T U V F G D E % W X R S Y Z [3 \] / 9 ^ _ ` a % ' 4 ' 5 9 b c d e ] ' 4 ! 6 ' 7 8 9 f g ] h ^ _ ` a ' ' 4 ' 5 9 b c d e] ' 4 ! 6 ' 7 8 9 i	= >	j k l
,	! \$ # \$ "	)	3 4 : , 0 ; < (= > \$? 1 . : , 0 ; @ A > \$? 1 . 1 (B (1 ? = (A 1 0 \$: - . : 1 0 \$? , m n o	= >	? @ A

BRBC817Q


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	50	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	500	mA
Collector Current - peak collector current	I_{CM}	1.0	A
Collector Power Dissipation	P_C	250	mW
Junction Temperature	T_J	150	°C

/ Electrical Characteristic Curve




/ Package Dimensions

UNIT: mm
前位



/ Marking Instructions



Q


6A

Note:

Q: Automobile halogen-free product Code

6A: Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1. Preheating: 150~200 °C, Time: 60~120sec.
2. Peak Temp.: 255±5 °C, Duration: 5±0.5sec.
3. Cooling Speed: 2~10 °C/sec.

/ Resistance to Soldering Heat test Conditions

260±5 °C 10±1 sec. Temp.: 260±5 °C Time: 10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7" x8	180×120×180	390×385×205

/ Notices